Revision Date: 13/08/2012

Revision: 4



SAFETY DATA SHEET Fosroc Galvafroid

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name Fosroc Galvafroid

Product No. 1590020, 1590022, 1590042, 1590080, 1590120

1.2. Relevant identified uses of the substance or mixture and uses advised against

<u>Identified uses</u> Rust-preventing primer.

1.3. Details of the supplier of the safety data sheet

Supplier: Fosroc Ltd

Drayton Manor Business Park

Coleshill Road Tamworth Staffordshire B77 2JU

+44 (0)1827 262222 +44 (0)1827 262444 uk@fosroc.com

1.4. Emergency telephone number

+44 (0) 1827 265 279 (08.30 to 17.00hrs Mon - Thu; 08.30 to 16.00hrs Fri)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (1999/45/EEC) Xn;R65. N;R50/53. R10.

2.2. Label elements

Contains: SOLVENT NAPHTHA

Labelling





Harmful Dangerous for the

Risk Phrases

R10 Flammable.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

Safety Phrases

S51 Use only in well-ventilated areas.

S57 Use appropriate containment to avoid environmental contamination.

S60 This material and its container must be disposed of as hazardous waste.

S61 Avoid release to the environment. Refer to special instructions/safety data

sheets.

S62 If swallowed, do not induce vomiting: seek medical advice immediately and

show this container or label.

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

ZINC POWDER - ZINC DUST (STAE	60-100%		
CAS-No.: 7440-66-6	EC No.:		
Classification (EC 1272/2008) Not classified.		Classification (67/548/EEC) N;R50/53	
SOLVENT NAPHTHA			10-30%
CAS-No.: 64742-95-6	EC No.: 265-199-0		
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT Single 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		Classification (67/548/EEC) Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.	
1,2,4-TRIMETHYLBENZENE			5-10%
CAS-No.: 95-63-6	EC No.: 202-436-9		
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT Single 3 - H335 Aquatic Chronic 2 - H411		Classification (67/548/EEC) R10 Xn;R20 Xi;R36/37/38 N;R51/53	
ZINC OXIDE			1-5%
CAS-No.: 1314-13-2	EC No.: 215-222-5		
Classification (EC 1272/2008) Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		Classification (67/548/EEC) N;R50/53	
MESITYLENE			1-59
CAS-No.: 108-67-8	EC No.: 203-604-4		
Classification (EC 1272/2008) Flam. Liq. 3 - H226 STOT Single 3 - H335 Aquatic Chronic 2 - H411		Classification (67/548/EEC) R10 Xi;R37 N;R51/53	
CHLORINATED PARAFFIN			1-59
CAS-No.: 85535-85-9	EC No.: 287-477-0		
Classification (EC 1272/2008) Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		Classification (67/548/EEC) N;R50/53.	

 REACTION PRODUCT WITH FATTY ACID AND AMINOETHYLPIPERAZINE

 CAS-No.: 92062-17-4
 EC No.: 295-532-5

 Classification (EC 1272/2008)
 Classification (67/548/EEC)

 Skin Irrit. 2 - H315
 Xi;R38,R41.

 Eye Dam. 1 - H318
 N;R50/53.

XYLENE

CAS-No.: 1330-20-7

EC No.: 215-535-7

Classification (EC 1272/2008)
Flam. Liq. 3 - H226
Acute Tox. 4 - H312
Acute Tox. 4 - H332
Skin Irrit. 2 - H315

CUMENE			< 1%
CAS-No.: 98-82-8	EC No.: 202-704-5		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 3 - H226		R10	
STOT Single 3 - H335		Xn;R65	
Asp. Tox. 1 - H304		Xi;R37	
Aquatic Chronic 2 - H411		N;R51/53	

The Full Text for all R-Phrases and Hazard Statements is Displayed in Section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Information

Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

<u>Ingestion</u>

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Drink plenty of water. Get medical attention immediately! Provide rest, warmth and fresh air.

Skin Contact

Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General Information

The severity of the symptoms described will vary dependant of the concentration and the length of exposure.

Inhalation.

Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion

The product causes irritation of mucous membranes and may cause abdominal discomfort if swallowed.

Skin Contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

Eye Contact

May cause severe irritation to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing Media

Fire can be extinguished using: Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

Hazardous Combustion Products

During fire, toxic gases (CO, CO2) are formed.

Unusual Fire & Explosion Hazards

FLAMMABLE.

Specific Hazards

Dust may form an explosive mixture in the atmosphere.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

Protective Measures In Fire

Wear full protective clothing

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

For personal protection, see section 8.

6.2. Environmental precautions

Do not allow to enter drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

6.4. Reference to other sections

For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
1,2,4-TRIMETHYLBENZENE	WEL	25 ppm	125 mg/m3			
CUMENE	WEL	25 ppm	125 mg/m3	50 ppm	250 mg/m3	Sk
MESITYLENE	WEL	25 ppm	125 mg/m3			
SOLVENT NAPHTHA	WEL	19 ppm				
XYLENE	WEL	50 ppm	220 mg/m3	100 ppm	441 mg/m3	Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective Equipment





Process Conditions

Use engineering controls to reduce air contamination to permissible exposure level.

Engineering Measures

Provide adequate general and local exhaust ventilation.

Respiratory Equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

Hand Protection

Use protective gloves.

Eye Protection

Wear approved safety goggles.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene Measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

AppearanceLiquidColourGreyOdourAromatic.SolubilityInsoluble in water

Initial Boiling Point and Boiling 155 - 181

Range:

 Vapour Pressure
 0.25 kPa 20

 Evaporation Rate
 0.20 (EtOH=1)

Viscosity6 PsFlash Point (°C)41°CAuto Ignition Temperature (°C)> 450

9.2. Other information

Volatile Organic Compound (VOC) 320 g/litre

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reaction with: Acids. Oxidising materials.

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Avoid contact with acids and oxidising substances.

10.5. Incompatible materials

Materials To Avoid

Acids, oxidising.

10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Health Warnings

INHALATION. Prolonged inhalation of high concentrations may damage respiratory system. SKIN CONTACT. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation. EYE CONTACT. May cause severe irritation to eyes. INGESTION. The product causes irritation of mucous membranes and may cause abdominal discomfort if swallowed.

Target Organs

Skin Eyes Respiratory system, lungs

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

The product contains a substance which is very toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

12.1. Toxicity

Acute Fish Toxicity

No data available.

12.2. Persistence and degradability

Degradability:

The product is not expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative Potential:

No data available on bioaccumulation.

12.4. Mobility in soil

Mobility:

The product contains substances which are insoluble in water and which sediment in water systems. The product contains volatile substances, which may spread in the atmosphere.

12.5. Results of PBT and vPvB assessment

Assessment not carried out but this product is believed not to be a PBT nor a vPvB.

12.6. Other adverse effects

When used and disposed of as intended no adverse environmental effects are foreseen

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

 Waste Class
 08-02-99

 Waste Class
 H9, H14

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

 UN No. (ADR/RID/ADN)
 1263

 UN No. (IMDG)
 1263

 UN No. (ICAO)
 1263

14.2 UN Proper shipping name

Proper Shipping Name PAINT RELATED MATERIAL (ZINC POWDER - ZINC DUST (STABILISED))

14.3 Transport hazard class(es)

ADR/RID/ADN Class

ADR/RID/ADN Class Class 3: Flammable liquids.

 ADR Label No.
 3

 IMDG Class
 3

 ICAO Class/Division
 3

Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group III

IMDG Packing group III

ICAO Packing group III

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant



14.6. Special precautions for user

 EMS
 F-E, S-E

 Emergency Action Code
 •3YE

 Hazard No. (ADR)
 30

 Tunnel Restriction Code
 (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not relevant.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Environmental Listing

Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980.

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG(108).

EU Legislation

System of specific information relating to Dangerous Preparations. 2001/58/EC.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

General Information

Only trained personnel should use this material.

Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision Date 13/08/2012

Revision 4

Risk Phrases In Full

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R20 Harmful by inhalation.

R65 Harmful: may cause lung damage if swallowed.
R36/37/38 Irritating to eyes, respiratory system and skin.

R37 Irritating to respiratory system.

R38 Irritating to skin.

R66 Repeated exposure may cause skin dryness or cracking.

R41 Risk of serious damage to eyes.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Hazard Statements In Full

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H315 Causes skin irritation.

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H312 Harmful in contact with skin.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.
H335 May cause respiratory irritation.

EUH066 Repeated exposure may cause skin dryness or cracking.

H411 Toxic to aquatic life with long lasting effects.
 H410 Very toxic to aquatic life with long lasting effects.

H400 Very toxic to aquatic life.

Disclaimer

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.